The Ground Water Model







William W. Woessner
Regents' Professor of Hydrogeology
Department of Geosciences
The University of Montana
Missoula, MT 59812
william.woessner@umontana.edu

September 27, 2006

What is a Model?



Floyd Tries to Go On Line

What is a Model?

Simplification of a real world setting.
Example-Road map is a model of the earth’s surface

Types of Models
Conceptual Model
Scale model
Analog model
Mathematical Model

Particle tracks-GW flow
Missoula Valley



Analytical Model

Numerical Model



Mathematical Models

Analytical Solution (equation)

Pumping Well- Predict
Drawdown (reduction in GW levels)



Numerical Model

Handles More Complex
GW Settings







Numerical Model

Break up the space and time into blocks and time Intervals. Node







Numerical Modeling Methods Assign data to cells or elements that represent a volume of aquifer material

Individual elements are then linked to adjacent cells and the GW model is created.



Formulate the GW Model

Cells in the three layered model

4,524

Assign values to cells

Assign boundary conditions

Set Initial Conditions



Figure 16. Block-centered finite-difference grid used for ground-water flow model of Desert Valley, Nevada.



Different amounts and distributions of data are required to solve different problems.

Generic Modeling

Interpretative Modeling

Predictive Modeling

Increasing Data Needs

Increasing Demand for Evidence of Simulation Match with Field Conditions

Modeling Process



Anderson and Woessner, 2004

Case Study Example



Figure 1. Location and general features of Desert Valley area.



Purpose: Examine the effects of mine dewatering on the ground-water conditions in Desert Valley, NV

Purpose is not to build a model!!!

Building the Conceptual Model

Physical Framework
Geology- nature, 3D extent
Surface topography and Soils
Hydrologic Features

Hydrologic Framework
Water Level Measurements
Surface Water Elevations
Surface Water Flows
Transmission and Storage
Properties of Earth Materials
Sources of Recharge and Discharge
Physical and Hydraulic Boundaries
Source and Sinks of Water
Water Quality Data

It's the Hydrogeology!!



Table 9. Estimated ground-water budget for predevelopment conditions (pre-1962), Desert Valley, Nevada

[All values in acre-feet per year]

Budget component	Estimated predevelopment conditions
Inflow	
Recharge from precipitation:	
From mountain block (p. 33, p. 34)	3,300 - 6,800
From sand dunes (p. 35)	500 - 1,000
Infiltration from rivers (p. 19)	700 - 4,700
Subsurface inflow:	
From Kings River Valley (p. 16)	900
From Quinn River Valley (p. 16)	300
Total inflow (rounded)	5,700 - 14,000
Outflow	
Evapotranspiration (p. 35)	10,000
Subsurface outflow:	
To Pine Valley (p. 19)	100 - 400
To Southwest (p. 19)	120 - 1,200
Total outflow (rounded)	10,000 - 12,000

Pre-simulation Water Balance

Critical!!!

In= Out +/- ΔStorage



Figure 16. Block-centered finite-difference grid used for ground-water flow model of Desert Valley, Nevada.

<u>Formulate the GW Model</u>

Cells in the three layered model
4,524
Assign values to cells
Assign boundary conditions

USGS MODFLOW
Numerical Model



Modeling Process



Anderson and Woessner, 2004

Execute and Calibrate the Model

Set Calibration Targets

1. **Differences between simulated and measured heads.**
2. **Differences between measured GW fluxes and simulated fluxes**
3. **Differences in the pre-simulation computed water balance and simulated water balance.**
4. **Differences in locations and rates of pre-simulation and simulation recharge and discharge**.

Using Trial and Error or Automated Parameter Estimation, the model is executed a number of times while adjusting model components such that differences between measured and simulated conditions are minimized

Pre-development 1962 Calibration

Pattern of water levels



Figure 20. Simulated potentiometric surface for layer 1 and water levels estimated on basis of field data, predevelopment conditions, Desert Valley, Nevada.



Figure 19. Frequency distribution of deviations between measured and simulated hydraulic heads for predevelopment simulation, Desert Valley, Nevada.

Overall measured and simulated head match

Simulated Flow at Boundaries Flow of Quinn River "agreed with estimates".

Simulated Water Balance

Table 11. Simulated ground-water budget for predevelopment conditions (pre-1962), Desert Valley, Nevada

[All values in acre-feet per year, rounded to two significant figures]

Budget component	Simulated predevelopment conditions
Inflow	
Recharge from precipitation:	
From mountain block	6,900
From sand dunes	440
Infiltration from rivers:	
Quinn River	2,600
Kings River	110
Subsurface inflow:	
From Kings River Valley	820
From Quinn River Valley	310
Total inflow	11,000
Outflow	
Evapotranspiration	9,100
Subsurface outflow:	
To Pine Valley	400
To Southwest	1,700
Total outflow	11,000

Original Water Balance
5,700 -14,000 Inflow
10,000 - 12,000 Outflow

1962 to 1991 GW Development Simulation



Figure 22. Estimates of net irrigation pumpage, mine-dewatering pumpage, and total ground-water withdrawals, by stress period, specified for development simulation, Desert Valley, Nevada.

History Matching

Transient Calibration

During modeling additional calibration parameter adjustment was completed to yield:

Water level and flux values in "…matched fairly well



Sensitivity Analyses

In this model:

1. Evaluated the sensitivity of model results to 5 hydrologic properties using 14 model simulations. Used head changes and calibrated flux rates at boundaries as baseline.
2. Halved and doubled parameter values.

Evaluation:

Model is most sensitive to recharge and plant use (ET) however absolute difference in mean head change is 10 ft.

Concluded :

Uncertainty in parameters does not effect general representation of the Gw system sufficiently to negate its use at this point.

Modeling Process



Anderson and Woessner, 2004

Assessing the Calibration and Determining Acceptability

What evidence do you have that a “reasonable representation has been produced?”

Preponderance of evidence /confirming observations documenting performance

Performance measured by closeness of fit with calibration targets and the character and nature of temporal and spatial data

Subjective judgment based on stated model purpose an supporting data.

Modeling Process



Anderson and Woessner, 2004

Prediction or Testing of Three Future De-watering Scenarios (no additional calibrations as no history)

Results of Predictions

1.Water level declines would not be localized around the mine.

2. Declines of 50 ft are simulated at 1 to 2 miles from the mine area.

3. The discharge of water to the wetland retards the expansion of water level declines.

4. Subsurface inflow form the Quinn River Valley occurs.

5. Based on water budgets a new equilibrium may be approached after 100 yr from the time the mine de-watering ceases.

"Past performance, as we are told, is no guarantee of future results"

The Wisdom of Crowds-James Surowiecki

Relationship of Reasonable Assurance to Bounding Analysis, Regulatory Limit, and Realistic Estimates



modified from NRC, 1990, GW Models and Regulatory Application p278

The Postaudit
(How good was the prediction?)

Anderson and Woessner, 1992

“ Can groundwater flow models accurately predict the future?”

“Postaudit…consists of examining the accuracy of a prediction made at least 10 years prior to the postaudit.

Assessments of short term predictions…are certainly useful but do not provide as rigorous a test of predictive ability.

Analyses of 11 POSTAUDITs found four general areas that effected model predictions:



1938 Grinnell Glacier
Glacier NP.

1. Future Stress History and Distribution

2. Parameter Values and Distributions

2005 Grinnell Glacier
Glacier NP.

2005

3. Calibration Conditions Not Appropriate for Predictions,

4. Conceptual Model.

Where Does That Leave Us?

Ground Water Models contain uncertainty, however, they are the only tool we have to assess complex settings!

We need to assess uncertainty using multiple conceptual models and present ranges of likely results to decision makers!